



408-2IN Indicator

Masibus' large digit display Model 408-2IN accepts universal process inputs. From these inputs the display can be scaled to remotely read in engineering units. Unregulated transmitter power supply is provided as standard on AC supply models.

For industrial applications demanding large displays while subjected to outdoor elements, high ambient light areas, Masibus offers series of Large Display Indicators in various sizes, where the LED display is visible from a long distance.

Model 408-2IN is micro-controller based design which accepts major industry standard inputs like RTD, thermocouples, mA, V, etc.

Model 408-2IN large digit displays are your flexible solution when a display needs to be viewed over distances as long as 80 feet (25 m). A rule of thumb is that viewing distance in feet is 40 times the digit height in inches, or in metric terms, the viewing distance in meters is digit height in millimeters divided by 2.

Depending on the selected digit size and mounting location, a Model 408-2IN display with normal brightness LEDs can be read across an entire plant floor, keeping the workforce informed of important process values at their work areas, eliminating the need to view from a small computer screen or local control panel.

Model 408-2IN displays are complete functional units, with all the necessary signal conditioning, power supply and display circuitry. Just apply power 230 VAC, connect your input signal, and display your reading. **This model is packaged in MS power coated enclosure of size 192(W) x 96(H) x 70(D) in mm which makes it unit rugged & reliable.**

Features

- Microprocessor based large display indicator
- High accuracy
- 8 selectable input types
- 4 digit LED display of 45mm (1.8") high
- Built-in Transmitter Power Supply
- 192 x 96mm enclosure
- Excellent long-term stability
- Easy configuration from front keys
- Digital calibration

Indicator (Model 408-2IN)

HARDWARE SPECIFICATIONS		408-2IN	HARDWARE SPECIFICATIONS		408-2IN
Measured Input Signal					
Number of Inputs	1		Storage conditions		
Input Type, Measurement Range & accuracy	As per table 1		Temperature	0 to 70 deg C	
Sampling Period	250 ms		Humidity	20 to 90% RH (non-condensing)	
Burn out detection	Available with TC, 1 to 5VDC, 4 to 20mA		Effect of operating conditions		
Burn out current	0.5 μ A		Effect of Ambient temperature	For T/C input, $\pm 0.1\%$ of F.S./ $^{\circ}$ C or less For Voltage input, $\pm 0.05\%$ of F.S./ $^{\circ}$ C or less For RTD input, $\pm 0.13\%$ of F.S./ $^{\circ}$ C or less	
Measuring current (RTD)	0.1 mA		Effect on power supply fluctuation	For analog input, within $\pm 0.005\%$ of F.S./ 10V	
Input Impedance	TC /mV / V: 1M Ω				
Allowable lead-wire resistance	15 Ω / wire or less Effect from allowable lead wire resistance: 0.66 $^{\circ}$ C / 10 Ω or less				
Allowable Input Voltage	TC / RTD: ± 10 V DC DC voltage: ± 20 V DC				
Noise Rejection Ratio					
Common Mode:	> 120 dB (50 Hz)				
Normal Mode:	> 45 dB (50 Hz)				
Reference junction compensation error	$\pm 1.5\ ^{\circ}$ C (20 to 45 $^{\circ}$ C)				
Applicable standard	ITS-90 or IPTS - 68				
24V DC Loop Power Supply for sensor	24 VDC $\pm 5\%$ @ 30 mA				
Display Unit Specification					
Process Value display	4- digit 7- segment Red LED (1.8")				
Display update rate	250 mS - TC, 400 mS - RTD				
Construction/Installation/Wiring					
Enclosure	General purpose				
Body construction	MS Powder coated				
Case color	Dark Grey				
Weight	Approximately 1 kg				
Dimensions	192W x 96H x 70D (all in mm)				
Mounting	Panel mount / Grid mount compatible				
Panel Cut-out	188(W) x 92(H) (all in mm)				
Wiring	2.5 Sq. mm Terminal				
Standard Accessories	2 mounting clamp, 250 Ω resistor				
Power supply/Isolation					
Power supply	230 VAC (-15% to +10%) @ 50Hz				
Power consumption	Less than 10 VA				
Isolation resistance	Between power supply terminal and ground terminal, 500V DC 50 M Ω				
Isolation Specifications					
Measured Input terminal	Isolated from other input terminals.				
24V DC Supply for Transmitter	Isolated from other input terminals				
Power supply terminal	Isolated from other input terminals and internal circuit.				
Ground terminal	Isolated from other input terminals and internal circuit.				
Environmental Conditions					
Normal Operating conditions					
Ambient Temperature	0 to 55 deg C				
Ambient humidity	20 to 90% RH (non-condensing)				
Warm up time	> 45 min				

TABLE 1

Input Type	Range	Measurement Accuracy
Thermocouples J	-100 to 1200 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
K	-100 to 1372 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
T	-100 to 400 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
R	0 to 1768 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
S	0 to 1768 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
TD	Pt-100 -199.9 to 850.0 $^{\circ}$ C	$\pm (0.25\% \text{ of FS} \pm 1 \text{ count})$
DC Voltage	1-5V -1999 to 9999	$\pm (0.1\% \text{ of FS} \pm 1 \text{ count})$
	0-5V -1999 to 9999	$\pm (0.1\% \text{ of FS} \pm 1 \text{ count})$

ORDERING CODE

Model	Input Type	APS	Mounting
408-2IN	X	XX	XX
2	J	A1	110Vac
3	K	A2	230Vac
4	T		
6	R		
7	S		
9	Pt-100,3W		
C	4-20mA		
D	0-20mA		
E	1-5Vdc		
F	0-5Vdc		

X - Specify from table

Head Office:
Masibus Automation And Instrumentation Pvt. Ltd.
B-30, GIDC Electronics Estate, Sector-25, Gandhinagar - 382044, Gujarat, India.
Tel: +91 79 2328725-79, Fax: +91 79 23287281-82.
E-mail: sales@masibus.com, Web: www.masibus.com

All specifications are subject to change without notice due to continuous improvements.
Doc. Ref. CB-2/408-2IN/R1/0110

Masibus Representative: